



1

6.1 Overview - Cross-Laminated Timber (CLT) Shear Wall Example

- This example features the seismic design of cross-laminated timber shear walls used in a three-story, six-unit townhouse cross-laminated timber building of platform construction
- The CLT shear wall design in this example includes:
 - Check of CLT shear wall shear strength
 - Check of CLT shear wall hold-down size and compression zone length for overturning
 - Check of CLT shear wall deflection for conformance to seismic drift



Figure 6-2. Elevation




Figure 6-3. Typical Floor Plan (first story openings shown)



Federal Emergency Management Agency

2

2

6.1 Overview - Useful Design Aid Resources

- The following documents are used in this example
 - ASCE/SEI 7-22 Minimum Design Loads and Associated Criteria for Buildings and Other Structures
 - AWC (2020). Special Design Provisions for Wind and Seismic (SDPWS), SDPWS-21, American Wood Council
 - AWC (2017). National Design Specification (NDS) for Wood Construction, NDS-18, American Wood Council, Leesburg, VA, 2017
 - APA (2020). Standard for Performance-Rated Cross-Laminated Timber, ANSI/APA PRG 320-19, APA, 2020
 - FEMA (2020a). NEHRP Recommended Seismic Provisions for New Buildings and Other Structures, Volume I: Part 1 Provisions and Part 2 Commentary, 2020 Edition, FEMA P-2082-1, prepared by the Building Seismic Safety Council of the National Institute of Buildings Sciences for Federal Emergency Management Agency



FEMA



Federal Emergency Management Agency

3

3

6.2 Background

- NEHRP (2020a) proposed additions for ASCE/SEI 7-22 Table 12.2-1 featuring cross-laminated timber (CLT) shear walls

Seismic Force-Resisting System	Detailing Requirements, ASCE/SEI 7-22 Section	R	Ω_0	C_d	Structural System Limitations Including Structural Height, h_n (ft) Limits ^d				
					Seismic Design Category				
					B	C	D	E	F
A. BEARING WALL SYSTEMS									
Cross laminated timber shear walls	14.5	3	3	3	65	65	65	65	65
Cross laminated timber shear walls with shear resistance provided by high aspect ratio panels only	14.5	4	3	4	65	65	65	65	65



FEMA




Federal Emergency Management Agency

4

4

6.2 Background

- Cross-laminated timber (CLT)
 - Usually 3, 5 or 7 layers of dimension lumber stacked in alternating directions and bonded together with adhesive
 - Research and development for CLT began in the early 1990s in Europe
 - The first production facilities established in 1994 in Austria, Germany and Switzerland
 - The term coined in 2000 at the COST E5 conference in Italy



CLT panel with layers stacked in alternating (crossing) directions



FEMA



Federal Emergency Management Agency

5

5

6.2 Background

- Cross-laminated timber (CLT)
 - Stadthaus, London, 2009
 - Residential
 - 9 stories
 - 9 weeks of CLT construction
 - 4 laborers
 - 1 supervisor



Photo credit: Will Pryce

Federal Emergency Management Agency

6



FEMA



6

6.2 Background



Photo credit: Will Pryce



FEMA



Federal Emergency Management Agency

7

7

6.2 Background




Photo credit: Will Pryce



FEMA



Federal Emergency Management Agency

8

8

6.2 Background



Ft. Drum, NY (4-story), 2017; Courtesy Jeff Morrow, Lendlease



FEMA





Federal Emergency Management Agency

9

9

6.2 Background

- FEMA P-695: Quantification of Building Seismic Performance Factors
 - Peer review throughout
 - Archetypes
 - Design methodology
 - Nonlinear time history analysis
 - Performance evaluation (CMR & ACMR)
- Project Documentation: van de Lindt, J., Amini, M. O. , Rammer, D., Line, P., Pei, S., and Popovski, M. (2022) "Determination of Seismic Performance Factors for Cross-Laminated Timber Shear Walls Based on the FEMA P695 Methodology." General Technical Report FPL-GTR-281, Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory.



FEMA




Federal Emergency Management Agency

10

10

6.2 Background



6.2 Background



6.2 Background



FEMA

Building Seismic Safety Council





Federal Emergency Management Agency

13

13

6.2 Background



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

14

14



Figure 6-2. Elevation




Figure 6-3. Typical Floor Plan (first story openings shown)

6.3 Cross-Laminated Timber Shear Wall Example Description

- A three-story, six-unit townhouse cross-laminated timber building of platform construction
- The CLT shear wall design in this example includes:
 - Check of CLT shear wall shear strength
 - Check of CLT shear wall hold-down size and compression zone length for overturning
 - Check of CLT shear wall deflection for conformance to seismic drift



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

15

15

6.3 Cross-Laminated Timber Shear Wall Example Description

Table 6-1: Weights of Roof/Ceiling, Floors, and Walls

Item	Description	Weight
Roof/Ceiling	Light-frame roof, gypsum board ceiling, roofing, insulation	25 psf
Floor	5-layer CLT (6.875 in. thick), gypsum board ceiling, flooring. Includes 8 psf of floor area for wall partitions	35 psf
Interior Walls	3-layer CLT (4.125 in. thick), light-frame wall, gypsum board finish, sound insulation	20 psf
Exterior Walls	3-layer CLT (4.125 in. thick), light-frame wall, gypsum board interior finish, stucco exterior, insulation	30 psf



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

16

16

6.3 Cross-Laminated Timber Shear Wall Example Description

Table 6-3: Design Coefficients and Factors for CLT Seismic Force-Resisting Systems (ASCE/SEI 7-22)

Seismic Force-Resisting System	Detailing Requirements, ASCE/SEI 7-22 Section	R	Ω_0	C_d	Structural Height, h_n , Limit Seismic Design Category B, C, D, E & F
Cross-laminated timber shear walls	14.5	3	3	3	65 feet
Cross-laminated timber shear walls with shear resistance provided by high aspect ratio panels only	14.5	4	3	4	65 feet



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

17

17

6.4 Seismic Forces

- Seismic base shear calculation assumptions:
 - $S_{DS} = 1.0$
 - $I_e = 1.0$
 - $R = 3$ (for CLT shear walls)
- Seismic base shear, V , per ASCE/SEI 7-22 Equation 12.8-2 (for short-period structures):

$$V = C_s W = \frac{S_{DS}}{(R/I)} W = \frac{1.0}{(3.0/1.0)} W = 0.333 W \text{ kips}$$

- The portion of base shear tributary to the CLT shear walls of interest is:

$$V_{(\text{Line 4})} = 42.3 \text{ kips}$$



FEMA


Building Seismic Safety Council



Federal Emergency Management Agency

18

18



19

6.5.1 Shear Capacity of Prescribed Connectors

- LRFD design unit shear capacity for seismic:

$$v_{s(seismic)} = \phi(n) \left(\frac{2605}{b_s} \right) C_G \quad (\text{SDPWS-21 Eq. B-2})$$

where:

- n = number of angle connectors along bottom of panel face
- 2,605 = connector nominal shear capacity (lb)
- b_s = individual CLT panel length (ft)
- C_G = CLT panel specific gravity factor which equals 1.0 for $G \geq 0.42$ specific gravity panels used in this example, and
- ϕ = resistance factor equal to 0.5 for seismic design

From SDPWS Figure C-B.1

Federal Emergency Management Agency 20

20

6.5.1 Shear Capacity of Prescribed Connectors

Table 6-5: CLT Shear Wall Connectors and LRFD Design Unit Shear Capacity

Story	Panel thickness	Panel length, b_s	Panel height, h	Number of connectors per panel at top and bottom panel edge	Number of connectors at each adjoining vertical panel edge	V_n , Nominal unit shear capacity, $(n \cdot 2605) / b_s$	$V_s^{(seismic)}$, LRFD design unit shear capacity, $(\phi = 0.5)$
	(in.)	(ft)	(ft)	(n)	$(n \times h / b_s)$	(plf)	(plf)
3	4.125	4.75	9.5	2	4	1,096	548
2	4.125	4.75	9.5	4	8	2,193	1,097
1	4.125	4.75	9.5	5	10	2,742	1,371




FEMA



Federal Emergency Management Agency

21

21



Federal Emergency Management Agency

22

22

6.5.2 Shear Capacity of CLT Panel

- For this 3-layer E1 grade CLT panel, the allowable stress design (ASD) in-plane shear unit shear capacity is converted to LRFD using NDS-2018 Table 10.3.1:

$$v_r' = \phi \lambda K_F F_v(t_v) = 0.75(1.0)(2.88)(9,700) = 20,849 \text{ plf}$$

where:

$$F_v(t_v) = 9,700 \text{ plf (ASD value from CLT panel manufacturer's evaluation report)}$$

- CLT panel in-plane unit shear capacity, $v_r' = 20,849 \text{ plf}$ is greater than the largest unit shear force story demand of 1,273 plf (from Table 6-4)

$$20,849 \text{ plf} \gg 1,273 \text{ plf}$$

- In-plane unit shear capacity value does not account for holes, cuts or other modifications



6.6.1 CLT Shear Wall Hold-down Design



Figure 6-1. Illustration of Rocking Behavior of Seven Individual Panels in A Multi-panel CLT Shear Wall Designed in Accordance with SDPWS-21 Appendix B




Figure 6-7. Free-body Diagram for the Tension End Panel of the CLT Multi-panel Shear Wall



6.6.1 CLT Shear Wall Hold-down Design


▪ $\sum M_o = 0$

$$T(b_{eff}) - vb_s h + wb_s \left(\frac{b_s}{2}\right) - T_T(b_{eff}) = 0 \quad (\text{SDPWS-21 Eq. C-B.1})$$

$$T = \frac{vb_s h - wb_s \left(\frac{b_s}{2}\right)}{b_{eff}} + T_T \quad (\text{SDPWS-21 Eq. C-B.2})$$

Table 6-6: Solution for Tension Force, T, for Hold-down Strength Requirement

Story	Unit shear force per foot of shear wall length	$V_{s(e seismic)}$, LRFD design unit shear capacity, ($\phi = 0.5$)	2 x $V_{s(e seismic)}$	T_T from story above	T for 2 x $V_{s(e seismic)}$ requirement for load combination 1.0E - 0.7D
	(plf)	(plf)	(plf)	(lb)	(lb)
3	477	548	1,097	0	11,293
2	1,009	1,097	2,194	11,293	34,540
1	1,273	1,371	2,742	34,540	63,968



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

25


25

6.6.1 CLT Shear Wall Hold-down Design

- The same screw attached hold-down is used for all locations with each having an LRFD design tension capacity of 17,678 lb and associated deflection of 0.253 in.

- 1st story walls to foundation, four hold-downs
 $4 \times 17,687 \text{ lb} = 70,748 \text{ lb} > 63,968 \text{ lbs}$
- 2nd story to top of 1st story, four hold-downs
 $4 \times 17,687 \text{ lb} = 70,748 \text{ lb} > 34,540 \text{ lbs}$
- 3rd story to top of 2nd story, two hold-downs
 $2 \times 17,687 \text{ lb} = 37,374 \text{ lb} > 11,293 \text{ lbs}$

- Check CLT panel for tension, row and group tear out



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

26

26

6.6.1 CLT Shear Wall Hold-down Design


- From SDPWS-21 Section B.3.4, hold-down device deformation for each story shall not exceed 0.185 in. for T forces from strength design load combinations (see Table 6-7)

Table 6-7: Solution for Tension Force, T, for Hold-down Deflection Requirement

Story	Unit shear force per foot of shear wall length	T for load combination
	(plf)	1.0E - 0.7D
3	477	4,714
2	1,009	14,604
1	1,273	27,472

- Deflection of most highly loaded hold-down is less than 0.185 in. The SDPWS-21 deflection limit is satisfied

$$\Delta_{hold-down} = \frac{27,472 \text{ lb}}{4(17,678 \text{ lb})} (0.253 \text{ in.}) = 0.098 \text{ in.} < 0.185 \text{ in.}$$



6.6.2 CLT Shear Wall Compression Zone

- Compression force, C, and length of compression zone, x, from compression end panel moment equilibrium

$$\sum M_o = 0$$

$$C \left(b_s - \frac{x}{2} \right) - v b_s h - w b_s \left(\frac{b_s}{2} \right) - C_T \left(b_s - \frac{x_T}{2} \right) = 0 \quad (\text{SDPWS-21 Eq. C-B.3})$$

$$C = F_{c\perp}'(t)(x) \left(\frac{12 \text{ in.}}{\text{ft}} \right) \quad (\text{SDPWS-21 Eq. C-B.4})$$

$$C = F_{c\parallel}'(t_{parallel})(x) \left(\frac{12 \text{ in.}}{\text{ft}} \right) \quad (\text{SDPWS-21 Eq. C-B.5})$$

- C and x summarized in Table 6-8





Figure 6-8. Free-body Diagram for the Compression End Panel of the CLT Multi-panel Shear Wall



6.6.2 CLT Shear Wall Compression Zone

Table 6-8: Solution for Compression Zone Length, x, and Force C

Story	Unit shear force per foot of shear wall length	Dead load, W_{DL}	Live load, W_{LL}	C_T , Compression from top	Compression zone length, x	C, for load combination $1.0E + 1.4D + 0.5L$
	(plf)	(plf)	(plf)	(lb)	(in.)	(lb)
3	477	190	0	0	2.00	5,257
2	1,009	793	690	5,257	7.64	20,144
1	1,273	793	690	20,144	4.56	36,545



- Check of CLT wall panel axial capacity is required



6.7 CLT Shear Wall Deflection

$$\delta_{SW} = \frac{576vb_s h^3}{E_{eff}(in-plane)} + \frac{vh}{GA_{eff}(in-plane)} + 3\Delta_{nail\ slip,h} + 2\Delta_{nail\ slip,v} \left(\frac{h}{b_s}\right) + \Delta_a \frac{h}{\sum b_s}$$

(SDPWS-21 Eq. B-1)

Total shear wall = deflection, δ_{SW}	Panel bending and shear +	Sliding +	Panel rotation +	Rigid body rotation



6.7 CLT Shear Wall Deflection

Table 6-9: CLT Shear Wall Deflection Components and Total Shear Wall Deflection, δ_{SW}

Story	$\frac{576vb_s h^3}{EI_{eff(in-plane)}}$	$\frac{vh}{GA_{eff(in-plane)}}$	$3\Delta_{nail\ slip,h} + 2\Delta_{nail\ slip,v} \left(\frac{h}{b_s}\right)$	$\Delta_d \frac{h}{\sum b_s}$	δ_{SW} , shear wall deflection
	(in.)	(in.)	(in.)	(in.)	(in.)
3	0.02	0.04	0.15	0.04	0.24
2	0.04	0.09	0.16	0.04	0.33
1	0.05	0.11	0.16	0.03	0.35

- For allowable story drift limit is $2.5\%h$ from ASCE/SEI 7-22 Table 12.12-1, corresponding allowable deflection calculated using, C_d , equal to 3 for cross-laminated timber shear walls:

$$\delta_e = \frac{0.025(h)}{C_d} = \frac{0.025(114 \text{ in.})}{3.0} = 0.95 \text{ in.} > \delta_{SW}$$



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency

31

31

6.8 References

- See the “Other Useful Design Aid Resources” in Section 6.1 for additional references.
- van de Lindt, J., Amini, M. O., Rammer, D., Line, P., Pei, S., and Popovski, M. (2022) “Determination of Seismic Performance Factors for Cross-Laminated Timber Shear Walls Based on the FEMA P695 Methodology.” General Technical Report FPL-GTR-281, Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory.
- FPIinnovations (2013). US CLT Handbook, Special Publication SP-529E. Pointe-Claire, QC, Canada.



FEMA

Building Seismic Safety Council



Federal Emergency Management Agency


32

32

Building Code Reference of SDPWS Standard

2021 IBC


- References 2021 SDPWS in Section 2305 for lateral design and construction



33

Building Code Reference of ASCE 7-22 Standard

**Targeted for reference
in 2024 IBC**



34

NEHRP Provisions



NEHRP Recommended Seismic Provisions for New Buildings and Other Structures

Volume I: Part 1 Provisions, Part 2 Commentary
FEMA P-2082-1 / September 2020




- 2020 *NEHRP Recommended Seismic Provisions for New Buildings and Other Structures* ([FEMA P-2082](#))

https://www.fema.gov/sites/default/files/2020-10/fema_2020-nehrp-provisions_part-1-and-part-2.pdf

35

NEHRP Provisions Design Examples



2020 NEHRP Recommended Seismic Provisions: Design Examples, Training Materials, and Design Flow Charts

FEMA P-2192-V1/November 2021

Volume I: Design Examples



- 2020 *NEHRP Recommended Seismic Provisions: Design Examples, Training Materials, and Design Flow Charts*, [FEMA P-2192](#)

- Volume 1: Design Examples

https://www.fema.gov/sites/default/files/documents/fema_nehrp_design-examples-training-materials_volume-1.pdf

36

Cross-Laminated Timber (CLT) Shear Wall

Thank You



FEMA



Federal Emergency Management Agency

37

37

Contact Slide

Philip Line
American Wood Council
pline@awc.org

M. Omar Amini
American Wood Council
oamini@awc.org



FEMA



Building Seismic
Safety Council

| BSSC



38